



FAS - NZ Pump Series Technology
Efficiency - Experience - Reliability



► **Benefits:**

- Compact construction
- High efficiency
- Low energy consumption

Model	Capacity, m ³ /h (l/m)	Differential pressure, bar	NPSH, m H ₂ O	Power consumption, kW	Inlet / Outlet, DN
NZ 40-6-12,5	40 (660)	6	2,7	12,5	80/65
NZ 40-8-15		8	2,7	15,0	
NZ 40-10-24		10	2,1	24,0	
NZ 60-5-15	60 (990)	5	2,8	15,0	125/100
NZ 60-7-20		7	2,8	20,0	
NZ 60-10-28		10	2,8	28,0	
NZ 80-5-24	80 (1320)	5	3,0	24,0	
NZ 80-7-24		7	3,0	24,0	
NZ 80-11-47		11	3,0	47,0	
NZ 100-5-24	100 (1660)	5	3,8	24,0	
NZ 100-7-28		7	3,8	28,0	
NZ 100-10-47		10	4	47,0	
NZ 150-5-28	150 (2490)	5	6,0	28,0	
NZ 150-7-36		7	6,0	36,0	
NZ 150-10-58		10	6,0	58,0	
NZ 200-5-58	200 (3320)	5	2,9	58,0	
NZ 200-7-80		7	2,9	80,0	
NZ 200-10-100		10	2,9	100,0	
NZ 260-5-68	260 (4310)	5	4,1	68,0	
NZ 260-7-100		7	4,1	100,0	
NZ 260-10-135		10	4,1	135,0	

Flüssiggas-Anlagen GmbH

Peiner Straße 217
38229 Salzgitter - Germany

Phone: +49 5341 8697-0
Fax: +49 5341 8697-11

E-Mail: info@fas.de
www.fas-engineering.de

www.fas.de