

I

Safety relief valves

Safety relief valve

- spring-loaded relief valve
- thread connection
- plastic protection cap
- body of brass



Order No.	Type (Reg0)	Connection	Total height, mm	Hexagon size, mm	Flow capacity, m ³ /min	Adjusted at (bar)	Weight, kg
28 301	RS3131	¾" M.NPSM	85	46	48,9	17,2	1,0
28 303	RS3132	1" M.NPSM	129	60	77,5	17,2	1,0
28 305	RS3135	¼" M.NPSM	141	68	118,0	17,2	1,0
28 382	RS3145	M45×2	139	68	187,2	15,6	1,0
28 869	RS3136	M36×2	135	60	134,3	15,6	1,0
28 875	RS3136	M36×2	135	60	134,3	17,0	1,0
90 904	RS3145	M45×2	139	68	187,2	17,0	1,0

Check device

for safety relief valves

- for exchange of relief valves without emptying of tank
- seal
- body of brass



Order No.	Type (Reg0)	Valve type	Internal thread	External thread	Total height, mm	Hexagon size, mm	Weight, kg
28 306	CD35	RS3135	1¼" F.NPSM	2" M.NPT	59	62	0,5
28 387	CD31	RS3131	¾" F.NPSM	1¼" M.NPT	59	46	0,5
28 388	CD32	RS3132	1" F.NPSM	1¼" M.NPT	59	46	0,5
28 389	CD45	RS3145	M45×2	2" M.NPT	59	62	0,5
28 854	CD36	RS3136	M36×2	1¼" M.NPT	58	52	0,5

Safety relief valves

for pipelines, mobile and stationary tanks, multivalves and duoports

- without protection cap

Please indicate the required setting pressure when placing your order. Valves 15281, 15291 and 15292 – without threaded connection for vent piping. Order number is depending on setting pressure.



Order No.	Type RegO	Connection NPT, "	Pressure range (bar)	Material	Pic.	Weight, kg
15 281	RegO 3127	¼	3...44	Brass	1	0,1
15 291	RegO SS8001	¼	10...31	Stainless steel		0,1
15 292	RegO SS8002	½	10...31			
15 282	RegO 3129	½	4...31	Brass		0,1
15 293	RegO SS8021	¼	10...31	Stainless steel		0,1
15 294	RegO SS8021	½	10...31			0,1
15 284	RegO 3131	¾	2...27	Brass	2	0,5
15 287	RegO W3132	1	3...34			1,2
15 288	RegO 8684	1	12...21		3	0,6
15 289	RegO 8685	1¼	7...20			1,0
15 311	RegO 3132	1¼	2...27		2	1,3
15 285	RegO 3135	1¼	7...19			1,5
15 312	RegO 3133	1½	6...19			2,1
15 314	RegO 7573	2	6...31		3	4,4
15 315	Fisher H280/H281...	2	10...25			4,2
15 316	RegO A8434 Fisher H720/H721	2	10...25	Steel	4	2,1
15 286	RegO A3149	2½	2...21		2	7,2
15 317	RegO A8436 Fisher H730/H731	3	10...25		5	5,2

Adaptor
 for attachment of vent piping


Order No.	Type RegO	For safety relief valve	Material	Connection, "	Pic.	Weight, kg
15 331	3129-10	RegO 3129	Brass	½ NPT female	1	0,06
15 334	7534-20	RegO 7534		3 NPT female	2	1,00
15 336	3132-10	RegO 3132		1¼ NPT female	1	0,20
15 328	3131-10	RegO 3131		1 NPT female		0,20
15 329	3133-10	RegO 3133		2 NPT female		0,50
15 330	3135-10	RegO 3135		2 NPT female		0,40
15 332	–	SV-A 12, A 22, A 23 SV-A 24, A 26, SV 805		½ NPT female	3	0,06
15 333	–	SV 486	Stainless steel	Rp 1½ female	4	0,20
15 335	–	SV-A 3		Rp 1½ female	3	0,30
15 337*	–	SV-A 12ES, A 14ES, SV-A 16ES, SV 805		½ NPT female		0,06
15 338*	–	SV-A 12ES, A 14ES		½ NPT female		0,06
			Steel, galvanized	½ NPT female		

Protective cap
 for relief valve


Order No.	Ventil Type	For relief valve type	Material	Weight, kg
15 403	RegO 3131-40	RegO 3131	Rubber	0,01
15 405	RegO 7545-40	RegO 3127, 3129		0,05
15 406	RegO 3132-40	RegO 3132	Steel	0,15
15 407	RegO 7534-40	RegO 7534		0,37
15 408	RegO 7584-40	RegO 8684	Rubber	0,09
15 409	RegO 7585-40	RegO 8685		0,14
15 411	Fisher P297	Fisher H720/721		0,10
15 412	Fisher P298	Fisher H730/731		0,15
15 413	RegO A8434-11B	RegO A8434		0,31
15 414	RegO A8436-11B	RegO A8436		0,10
15 415	RegO 3133-40	RegO 3133		0,05
15 416	RegO 3149-40	RegO A3149		0,10
15 417	RegO 3135-40	RegO 3135		0,10
15 401	–	SV-A 12/A 22/A 23/A 24/A 26/12ES/14ES/16 ES, SV 805	Plastics	0,01
15 404	–	SV-A 3		0,01
15 410	–	SV 486, SV 741		0,09